



MULTI SHAKING INCUBATOR



DK-SI 0504R



DK-SI 0404R

General Features

- Various space save models with multi rooms and multi shakers.
- Testing difference operation under different condition rooms.
- Brushless Motor adaption without noise and vibration.
- So many various racks for flasks, micro plates, test tubes and etc.



Specification

Model	DK-SI 0402R	DK-SI 0404R
Type	2 Room 2 Shaker	4 Room 4 Shaker
Dimension(IN)	650 x 600 x 500(H)mm x 2 Room	650 x 600 x 500(H)mm x 4 Room
Dimension(OUT)	830 x 870 x 1750(H)mm	1800 x 870 x 1750(H)mm
Holder Plate(Total)	250ml x 50EA	250ml x 100EA
Temp. Range	0°C to 60°C ±0.2°C	
Temp. Controller	Digital P.I.D Controller	
Speed Controller	Digital Display Feed back Speed Controller	
Timer	Digital Timer 99hr 59min. or Infinity	
Power(AC 220V, 60HZ)	2.5KW	4.5KW

Model	DK-SI 0502	DK-SI 0504
Shaker	2 Shaker (1 Room)	4 Shaker (1 Room)
Dimension(IN)	650 x 600 x 1100(H)mm	1300 x 600 x 1100(H)mm
Dimension(OUT)	830 x 870 x 1700(H)mm	1480 x 870 x 1700(H)mm
Holder Plate(Total)	250ml x 50EA	250ml x 100EA
Temp. Range	0°C to 60°C ±0.2°C	
Temp. Controller	Digital P.I.D Controller	
Speed Controller	Digital Display Feed back Speed Controller	
Timer	Digital Timer 99hr 59min. or Infinity	
Power(AC 220V, 60HZ)	1.8KW	2.5KW

! The instruments have been tested in 220V, 60Hz power condition. There can be performance difference according as power condition of each country

Optional Accessory

- 100ml, 250ml, 500ml, 1000ml, 2000ml Flask Hoder Rack and Spring Rack