



# SHAKING INCUBATOR



DK-SI 030-L



Open Feature

## General Features

### ■ Brushless Motor

Since there is no brush, there is no need for repair and maintenance for the motor. Has less noise and feed-back control thus maintains detailed revolution speed.

### ■ Reciprocal Type

Orbital Type is the basic specification, and can also produce Reciprocal Type according to the experiment purpose.

## Specification

Model	DK-SI 030	DK-SI 030-L
Temp. Range	0°C~60°C	
Light Bank	NO	40W F.L ×2EA
Light Controller	NO	24Hr. Day & Night Controller
Temp. Controller	Digital PID Controller	
Temp. Accuracy	Better than ±0.2°C at 37°C	
Speed Controller	Digital Display Feed Back Speed Controller	
Speed Range	20~250RPM	
Dimension(IN)	600 ×570 ×800(H)mm	
Dimension(OUT)	950 ×820 ×1490(H)mm	
Circulation Fan	5" Convection Fan *2EA	
Motor	Brushless AC Motor	
Standard Plate	250ml ×25EA	
Door Packing	Magnetic Packing Door with Window	
Shelves	Adjustable 2EA	
Timer	99Hr. 59Min.	
Safety Device	Hydraulic Temperature Controller	
Power	110V, 220 ~ 240V, 50 / 60Hz, 1.6Kw	

**!** The instruments have been tested in 220V, 60Hz power condition. There can be performance difference according as power condition of each country

## Optional Accessory

Holder	100ml	250ml	500ml	1000ml	2000ml	Spring Rack
DK-SI 030	42EA	25EA	16EA	9EA	4EA	530 x 500mm